

# Safety Data Sheet

according to OSHA Hazard Communication  
29 CFR Part 1910.1200

## SECTION 1. Identification

**Product Name:** OMNIWAX® #1622 Urethane Mold Release

**24 Hour Emergency: Chem-Tel Inc.: 1-800-255-3924**

NOTE: Chem-Tel Inc. emergency number to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals

Supplied by: B & S Products Corp.  
1917 Eisenhower Drive N.  
Goshen, IN 46526  
(574) 537-0770  
E-Mail: b\_and\_s@frontier.com

## SECTION 2. Hazard(s) Identification

\*\*\* **EMERGENCY OVERVIEW** \*\*\*: May be fatal if swallowed. May be fatal if inhaled. Flammable liquid and vapor.

### GHS Classification

Acute Tox. 3, Flam. Liq. 2, STOT SE 3 NE, Skin Irrit. 2

### Symbol(s) of Product



### Signal Word

Danger

### GHS HAZARD STATEMENTS

Acute Toxicity, Inhalation, category 3	H331 Toxic if inhaled.
Flammable Liquid, category 2	H225 Highly flammable liquid and vapor.
STOT, single exposure, category 3, NE	H336 May cause drowsiness or dizziness.
Skin Irritation, category 2	H315 Causes skin irritation.

### GHS PRECAUTIONARY STATEMENTS

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352 IF ON SKIN:	Wash with plenty of water
P303+P361+P353 IF ON SKIN (or hair):	Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 IF INHALED:	Remove person to fresh air and keep comfortable for breathing.

# OMNIWAX<sup>®</sup> #1622 Urethane Mold Release

P311 Call a POISON CENTER/doctor/physician

P312 Call a POISON CENTER/doctor/physician if you feel unwell.

P321 Specific treatment (see first aid section on this label).

P332+P313 If skin irritation occurs: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P370+P378 In case of fire: Use appropriate method to extinguish.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

## SECTION 3. Composition/Information on Ingredients

Chemical Name	CAS-No.	Wt. %	GHS Symbols	GHS Statements
Aliphatic Hydrocarbon	64742-49-0	75-99	GHS02-GHS06	H225-315-331-336

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

## SECTION 4. First-Aid Measures

**FIRST AID - EYE CONTACT:** Remove contact lenses if worn. Immediately flush eyes with water. Flush eyes with water for a minimum of 15 minutes, occasionally lifting and lowering upper lids. Get medical attention promptly.

**FIRST AID - SKIN CONTACT:** Immediately flush skin with plenty of water. Remove clothing. Get medical attention immediately. Wash clothing separately and clean shoes before reuse.

**FIRST AID - INHALATION:** Rescuers should put on appropriate protective gear. Remove from area of exposure. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Keep victim warm. Get immediate medical attention. To prevent aspiration, keep head below knees.

**FIRST AID - INGESTION:** Do not induce vomiting. Do not give liquids. Obtain emergency medical attention.

## SECTION 5. Fire-Fighting Measures

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Flammable liquid and vapor. Vapors/dust may form explosive mixture with air. Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. Also, do not reuse container without commercial cleaning or reconditioning. Closed container may explode under extreme heat. Can release vapors that form explosive mixtures at or above the flashpoint.

**SPECIAL FIREFIGHTING PROCEDURES:** As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Water spray to cool containers or protect personnel. Use with caution. Avoid use of solid water streams. Water spray and foam must be applied carefully to avoid frothing. For large fires: Water fog, use fog to control vapors; For small fires: dry chemical, carbon dioxide, and foam.

**EXTINGUISHING MEDIA:** None Known

## SECTION 6. Accidental Release Measures

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Avoid runoff into storm sewers and ditches which lead to waterways. Use only non-combustible material for clean-up. Remove from surface by skimming or with suitable absorbents. Recover by pumping (use an explosion proof or hand pump). Use clean, non-sparking tools to collect absorbed materials. Eliminate all ignition sources. Prevent additional discharge of material if able to do so safely. If leak or spill has not ignited, use water spray to disperse the vapors. Do not touch or walk through spilled material. Stay upwind of spill. Ventilate spill area. Wear appropriate personal protective equipment. (See Exposure

# OMNIWAX® #1622 Urethane Mold Release

Controls / Personal Protection Section.)A vapor suppressing foam may be used to reduce vapors. Evacuate unnecessary personnel.

## SECTION 7. Handling and Storage

**HANDLING:** Use only in a well ventilated area. Follow all SDS/label precautions even after containers are emptied because they may retain product residues. Ground and bond containers when transferring material. Use spark-proof tools and explosion proof equipment. Avoid contact with eyes, skin, and clothing. Avoid breathing vapor, fumes or mist. Take precautionary measures against static discharge.

**STORAGE:** Containers can build up pressure if exposed to heat (fire). Keep away from heat, sparks, and flame. Keep container closed when not in use. Protect from direct sunlight. Store containers in a cool, well ventilated place. Static Discharge, materials can accumulate static charges which can cause an incendiary electrical discharge. Material is a static accumulator which has the potential of forming ignitable vapor-air mixtures in storage tanks.

## SECTION 8. Exposure Controls/Personal Protection

### Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH-TLV STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
Aliphatic Hydrocarbon	5 mg/m <sup>3</sup>	N.D.	5 mg/m <sup>3</sup>	N.D.

**MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation**  
**Sk = Skin Sensitizer N.E. = Not Established**

### Personal Protection

**RESPIRATORY PROTECTION:** Wear a MSHA/NIOSH approved (or equivalent) full-facepiece airline respirator in the positive pressure mode with emergency escape provisions.

**SKIN PROTECTION:** Wear impervious gloves to prevent contact with the skin. Wear protective gear as needed - apron, suit, boots. Wear long sleeves when contact is likely to occur.

**EYE PROTECTION:** Wear safety glasses with side shields (or goggles) and a face shield.

**OTHER PROTECTIVE EQUIPMENT:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

**HYGENIC PRACTICES:** Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and wash before reuse. Avoid breathing vapors. Do not eat, drink, or smoke in areas where this material is used.

## SECTION 9. Physical and Chemical Properties

**Appearance:** Clear, transparent liquid

**Physical State:** Liquid

**Odor:** Typical

**Odor Threshold:** N.D.

**Density, g/cm<sup>3</sup>:** 0.761

**pH:** N.D.

**Freeze Point, °C:** N.D.

**Viscosity:** N.D.

**Solubility in Water:** Slight

**Explosive Limits, vol%:** 1.3 - 10.2

**Boiling Range, °C:** 245 - 291

**Flash Point, °F:** 65

**Evaporation Rate:** No Information

**Auto-ignition Temp., °C:** N.D.

**Vapor Density:** N.D.

**Vapor Pressure:** N.D.

(See "Other information" Section for abbreviation legend)

## SECTION 10. Stability and Reactivity

**STABILITY:** No Information

**CONDITIONS TO AVOID:** Avoid impact, friction, heat, sparks, flame and source of ignition.

**INCOMPATIBILITY:** Keep away from acids. Prevent contact with strong oxidizing agents. Keep separate from alkalis.

**HAZARDOUS DECOMPOSITION PRODUCTS:** During combustion carbon monoxide may be formed. During combustion carbon dioxide may be formed.

**HAZARDOUS POLYMERIZATION:** No Information

# OMNIWAX<sup>®</sup> #1622 Urethane Mold Release

## SECTION 11. Toxicological Information

### Information on Toxicological Effects

**EFFECTS OF OVEREXPOSURE - INHALATION:** May be fatal if inhaled. Vapors can cause irritation of the respiratory tract. High concentrations can cause headache, nausea, weakness, lightheadedness, and stupor (CNS depression).

**EFFECTS OF OVEREXPOSURE - SKIN CONTACT:** Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash). Personnel with pre-existing skin disorders should avoid contact with this product. May cause skin irritation.

**EFFECTS OF OVEREXPOSURE - EYE CONTACT:** Contact with the eye may cause moderate irritation.

**EFFECTS OF OVEREXPOSURE - INGESTION:** This material may be harmful or fatal if swallowed. Irritating to mouth, throat, and stomach. Harmful or fatal if liquid is aspirated into lungs. Can be readily absorbed by the stomach and intestinal tract. Symptoms include burning sensation of the mouth and esophagus, nausea, vomiting, diarrhea, dizziness, staggering gait, drowsiness, loss of consciousness and delirium as well as additional central nervous system effects.

**EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:** Overexposure may cause nervous system damage. Significant exposure to this chemical may adversely affect people with chronic disease of the respiratory system, skin, and/or eyes. Significant exposure to this chemical may adversely affect people with chronic disease of the central nervous system. Possible brain damage from overexposure. Chronic effects of ingestion and subsequent aspiration into the lungs may cause pneumatocele (lung cavity) formation and chronic lung dysfunction.

### Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Name according to EEC</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
64742-49-0	Aliphatic Hydrocarbon	>5,170	>2,000	>7.63

## SECTION 12. Ecological Information

**ECOLOGICAL INFORMATION:** No Information

## SECTION 13. Disposal Considerations

Always dispose of any waste in accordance with all local, state, and federal regulations.

**DISPOSAL METHOD:** Dispose of waste in accordance with all local, state and federal regulations.

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Avoid runoff into storm sewers and ditches which lead to waterways. Use only non-combustible material for clean-up. Remove from surface by skimming or with suitable absorbents. Recover by pumping (use an explosion proof or hand pump). Use clean, non-sparking tools to collect absorbed materials. Eliminate all ignition sources. Prevent additional discharge of material if able to do so safely. If leak or spill has not ignited, use water spray to disperse the vapors. Do not touch or walk through spilled material. Stay upwind of spill. Ventilate spill area. Wear appropriate personal protective equipment. (See Exposure Controls / Personal Protection Section. )A vapor suppressing foam may be used to reduce vapors. Evacuate unnecessary personnel.

## SECTION 14. Transport Information

<b>DOT Proper Shipping Name:</b>	Petroleum distillates, n.o.s.	<b>Packing Group:</b>	II
<b>DOT Hazard Class:</b>	3	<b>Hazard SubClass:</b>	No Information
<b>DOT UN/NA Number:</b>	UN1268	<b>Resp. Guide Page:</b>	128

# OMNIWAX<sup>®</sup> #1622 Urethane Mold Release

## SECTION 15. Regulatory Information

### U.S. Federal Regulations:

#### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

None Known

#### SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

#### TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA components exist in this product.

### U.S. State Regulations:

#### NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product.

No NJ Right-To-Know components exist in this product.

#### PENNSYLVANIA RIGHT-TO-KNOW:

The following non-hazardous ingredients are present in the product are at or greater than 3%.

No PA Right-To-Know components exist in this product.

#### CALIFORNIA PROPOSITION 65 CARCINOGENS

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

No Proposition 65 Carcinogens exist in this product.

#### CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

No Proposition 65 Reproductive Toxins exist in this product.

## SECTION 16. Other Information

Revision Date: 4/30/2015

Supersedes Date: New SDS

Datasheet produced by: B & S Products Corp.

### HMIS Ratings:

Health: 1      Flammability: 3      Reactivity: 0      Personal Protection: X

Volatile Organic Compounds, gr/ltr: 100

DISCLAIMER: THE VOLATILE ORGANIC COMPOUND (VOC) CONTENT REPORTED HEREIN, IF ANY, IS BASED ON A MATERIAL VOC CALCULATION. NOTE THAT SEVERAL METHODS ARE USED FOR CALCULATING VOC CONTENT AND THAT STANDARDS/ REQUIREMENTS REGARDING VOC CONTENT VARY BY LOCATION/JURISDICTION. ACCORDINGLY, B & S PRODUCTS MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, REGARDING THIS MATERIAL'S COMPLIANCE WITH VOC STANDARDS/ REQUIREMENTS APPLICABLE IN LOCATIONS/JURISDICTIONS WHERE THIS MATERIAL MAY BE SOLD OR USED.

# OMNIWAX<sup>®</sup> #1622 Urethane Mold Release

## Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H331 Toxic if inhaled.

H336 May cause drowsiness or dizziness.

## Icons for GHS Pictograms shown in Section 3 describing each ingredient:

### GHS02



### GHS06



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

The information on this SDS was obtained from sources which we believe to be reliable. However, the information provided is without any warranty, expressed or implied, regarding its correctness. Some information presented and conclusions drawn herein are from sources other than direct test data on the product itself. The information and recommendations are offered for the user's consideration and examination and should be used to make an independent determination of the methods to safeguard workers and the environment. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For these reasons we do not assume responsibility and expressly disclaim any liability for loss, damage, or expense arising out of or in any way connected with handling, storage, use, or disposal of this product. If the product is used as a component in another product, this MSDS may not be applicable. It is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.