

Safety Data Sheet

according to OSHA Hazard Communication
29 CFR Part 1910.1200

SECTION 1. Identification

Product Name: OMNIWAX® #1628-B Release Agent

24 Hour Emergency: Chem-Tel Inc.: 1-800-255-3924

NOTE: Chem-Tel Inc. emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.

Supplied by: B & S Products Corp.
1917 Eisenhower Drive N.
Goshen, IN 46526
(574) 537-0770
E-Mail: b_and_s@frontier.com

SECTION 2. Hazard(s) Identification

*** EMERGENCY OVERVIEW ***: Flammable liquid and vapor. May be fatal if swallowed.

GHS Classification

Asp. Tox. 1, Carc. 2, Flam. Liq. 3, STOT RE 2, STOT SE 3 NE, STOT SE 3 RTI, Skin Irrit. 2

Symbol(s) of Product



Signal Word

Danger

GHS HAZARD STATEMENTS

Flammable Liquid, category 3

Aspiration Hazard, category 1

Skin Irritation, category 2

STOT, single exposure, category 3, RTI

STOT, single exposure, category 3, NE

Carcinogenicity, category 2

STOT, repeated exposure, category 2

H226 Flammable liquid and vapor.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

GHS PRECAUTIONARY STATEMENTS

P201

P202

P210

P240

P241

P242

P243

P260

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

OMNIWAX® #1628-B Release Agent

P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician
P302+P352	IF ON SKIN: Wash with plenty of water
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a POISON CENTER/doctor/physician if you feel unwell.
P314	Get medical advice/attention if you feel unwell.
P321	Specific treatment (see first aid section on this label).
P331	Do NOT induce vomiting.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire: Use appropriate method to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 3. Composition/Information on Ingredients

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
Aliphatic hydrocarbon	64742-47-8	75-100	GHS02-GHS07-GHS08	H226-315-335-336-351-373

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

SECTION 4. First-Aid Measures

FIRST AID - EYE CONTACT: Immediately flush eyes with water. Flush eyes with water for a minimum of 15 minutes, occasionally lifting and lowering upper lids. Get medical attention promptly. Remove contact lenses if worn.

FIRST AID - SKIN CONTACT: Remove contaminated clothing. Wash skin with soap and water. Get medical attention. Wash clothing separately and clean shoes before reuse.

FIRST AID - INHALATION: Rescuers should put on appropriate protective gear. Remove from area of exposure. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Keep victim warm. Get immediate medical attention. To prevent aspiration, keep head below knees.

FIRST AID - INGESTION: Do not induce vomiting. Do not give liquids. Obtain emergency medical attention.

SECTION 5. Fire-Fighting Measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: Flammable liquid and vapor. Can form explosive mixtures at temperatures at or above the flashpoint. Vapors/dust may form explosive mixture with air. Vapors can travel to a source of ignition and flash back. Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. Also, do not reuse container without commercial cleaning or reconditioning.

SPECIAL FIREFIGHTING PROCEDURES: As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Evacuate all unnecessary personnel. Shut down motors, pumps, electrical service and eliminate all sources of ignition. Avoid use of solid water streams. Water spray to cool containers or protect personnel. Use with caution. Water runoff can cause environmental damage. Dike and collect water used to fight fire

OMNIWAX® #1628-B Release Agent

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam, Water Fog

SECTION 6. Accidental Release Measures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Wear appropriate personal protective equipment. (See Exposure Controls / Personal Protection Section.) Eliminate all ignition sources. Prevent additional discharge of material if able to do so safely. Do not touch or walk through spilled material. Avoid runoff into storm sewers and ditches which lead to waterways. Ventilate spill area. Stay upwind of spill. A vapor suppressing foam may be used to reduce vapors. Collect spilled materials for disposal. Use only non-combustible material for clean-up. Use clean, non-sparking tools to collect absorbed materials. Remove from surface by skimming or with suitable absorbents. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Recover by pumping (use an explosion proof or hand pump).

SECTION 7. Handling and Storage

HANDLING: Use only in a well ventilated area. Avoid breathing vapor, fumes or mist. Avoid contact with eyes, skin, and clothing. When transferring, follow proper grounding procedures. Use spark-resistant tools. Do not load into compartments adjacent to heated cargo. Use explosion proof equipment. Always open containers slowly to allow any excess pressure to vent. Follow all MSDS/label precautions even after containers are emptied because they may retain product residues.

STORAGE: Keep away from heat, sparks, and flame. Containers can build up pressure if exposed to heat (fire). Store containers in a cool, well ventilated place. Keep container closed when not in use. Protect from direct sunlight. Static Discharge, materials can accumulate static charges which can cause an incendiary electrical discharge. Material is a static accumulator which has the potential of forming ignitable vapor-air mixtures in storage tanks.

SECTION 8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH-TLV STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
Aliphatic hydrocarbon	100 ppm	N.D.	500 ppm	N.D.

Personal Protection

RESPIRATORY PROTECTION: Wear a MSHA/NIOSH approved (or equivalent) full-facepiece airline respirator in the positive pressure mode with emergency escape provisions.

SKIN PROTECTION: Wear impervious gloves to prevent contact with the skin. Wear long sleeves when contact is likely to occur. Wear protective gear as needed - apron, suit, boots.

EYE PROTECTION: Wear safety glasses with side shields (or goggles) and a face shield.

OTHER PROTECTIVE EQUIPMENT: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

HYGIENIC PRACTICES: Do not eat, drink, or smoke in areas where this material is used. Avoid breathing vapors. Remove contaminated clothing and wash before reuse. Wash thoroughly after handling. Wash hands before eating.

SECTION 9. Physical and Chemical Properties

Appearance: Clear transparent to whitish

Odor: Typical

Density, g/cm³: 0.782

Freeze Point, °F: N.D.

Solubility in Water: Insoluble

Boiling Range, °F: 318 - 386

Evaporation Rate: 0.21 (n-butyl acetate=1)

Vapor Density: 5 (air=1)

(See "Other information" Section for abbreviation legend)

Physical State: Liquid

Odor Threshold: N.D.

pH: N.D.

Viscosity: N.D.

Explosive Limits, vol%: 0.8 - 6.0

Flash Point, °F: 104

Auto-ignition Temp., °F: N.D.

Vapor Pressure: N.D.

SECTION 10. Stability and Reactivity

STABILITY: No Information

CONDITIONS TO AVOID: Avoid impact, friction, heat, sparks, flame and source of ignition.

INCOMPATIBILITY: Keep separate from alkalis. Prevent contact with strong oxidizing agents. Keep away from acids.

HAZARDOUS DECOMPOSITION PRODUCTS: During combustion carbon monoxide may be formed. During combustion carbon dioxide may be formed.

HAZARDOUS POLYMERIZATION: No Information

SECTION 11. Toxicological Information

Information on Toxicological Effects

EFFECTS OF OVEREXPOSURE - INHALATION: Vapors can cause irritation of the respiratory tract. High concentrations can cause headache, nausea, weakness, lightheadedness, and stupor (CNS depression).

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Contact with skin may cause mild irritation. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash). Personnel with pre-existing skin disorders should avoid contact with this product.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: May cause eye irritation.

EFFECTS OF OVEREXPOSURE - INGESTION: This material may be harmful or fatal if swallowed. Harmful or fatal if liquid is aspirated into lungs. Irritating to mouth, throat, and stomach. Can be readily absorbed by the stomach and intestinal tract. Symptoms include burning sensation of the mouth and esophagus, nausea, vomiting, diarrhea, dizziness, staggering gait, drowsiness, loss of consciousness and delirium as well as additional central nervous system effects.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Possible brain damage from overexposure. Overexposure may cause nervous system damage. Chronic effects of ingestion and subsequent aspiration into the lungs may cause pneumatocele (lung cavity) formation and chronic lung dysfunction. Significant exposure to this chemical may adversely affect people with chronic disease of the respiratory system, central nervous system, kidney, liver, skin, and/or eyes.

Primary Route(s) of Entry: Eye Contact, Ingestion, Inhalation, Skin Contact

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Name according to EEC</u>	<u>Oral LD50, mg/kg</u>	<u>Dermal LD50, mg/kg</u>	<u>Vapor LC50, mg/L</u>
64742-47-8	Aliphatic hydrocarbon	>5,000	>2,000	>20.0

SECTION 12. Ecological Information

ECOLOGICAL INFORMATION: No Information

SECTION 13. Disposal Considerations

Always dispose of any waste in accordance with all local, state, and federal regulations.

DISPOSAL METHOD: Dispose of waste in accordance with all local, state and federal regulations.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASE OR SPILLED: Wear appropriate personal protective equipment. (See Exposure Controls / Personal Protection Section.) Eliminate all ignition sources. Prevent additional discharge of material if able to do so safely. Do not touch or walk through spilled material. Avoid runoff into storm sewers and ditches which lead to waterways. Ventilate spill area. Stay upwind of spill. A vapor suppressing foam may

OMNIWAX® #1628-B Release Agent

be used to reduce vapors. Collect spilled materials for disposal. Use only non-combustible material for clean-up. Use clean, non-sparking tools to collect absorbed materials. Remove from surface by skimming or with suitable absorbents. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Recover by pumping (use an explosion proof or hand pump).

SECTION 14. Transport Information

DOT Proper Shipping Name: Petroleum distillates, n.o.s. (naphtha solvent) - Combustible Liquid

Packing Group: III

DOT Hazard Class: No Information

Hazard SubClass: No Information

DOT UN/NA Number: UN1268

Resp. Guide Page: 128

SECTION 15. Regulatory Information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No SARA 313 components exist in this product

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA components exist in this product.

U.S. State Regulations:

NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product.

No NJ Right-To-Know components exist in this product.

PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product are at or greater than 3%.

No PA Right-To-Know components exist in this product.

CALIFORNIA PROPOSITION 65 CARCINOGENS

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

No Proposition 65 Carcinogens exist in this product.

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

No Proposition 65 Reproductive Toxins exist in this product.

SECTION 16. Other Information

Revision Date: 4/30/2015

Supersedes Date: New SDS

Datasheet produced by: B & S Products Corporation

OMNIWAX® #1628-B Release Agent

HMIS Ratings:

Health: 1

Flammability: 2

Reactivity: 0

Personal Protection: X

Volatile Organic Compounds, gr/ltr: 100

DISCLAIMER: THE VOLATILE ORGANIC COMPOUND (VOC) CONTENT REPORTED HEREIN, IF ANY, IS BASED ON A MATERIAL VOC CALCULATION. NOTE THAT SEVERAL METHODS ARE USED FOR CALCULATING VOC CONTENT AND THAT STANDARDS/ REQUIREMENTS REGARDING VOC CONTENT VARY BY LOCATION/JURISDICTION. ACCORDINGLY, B & S PRODUCTS MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, REGARDING THIS MATERIAL'S COMPLIANCE WITH VOC STANDARDS/REQUIREMENTS APPLICABLE IN LOCATIONS/JURISDICTIONS WHERE THIS MATERIAL MAY BE SOLD OR USED.

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H226	Flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:

GHS02



GHS07



GHS08



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

The information on this SDS was obtained from sources which we believe to be reliable. However, the information provided is without any warranty, expressed or implied, regarding its correctness. Some information presented and conclusions drawn herein are from sources other than direct test data on the product itself. The information and recommendations are offered for the user's consideration and examination and should be used to make an independent determination of the methods to safeguard workers and the environment. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For these reasons we do not assume responsibility and expressly disclaim any liability for loss, damage, or expense arising out of or in any way connected with handling, storage, use, or disposal of this product. If the product is used as a component in another product, this SDS may not be applicable. It is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.